

4MP(2K) IR IK10 IP67 POE Network Dome Camera (built-in mic)



- IR POE Dome Camera
- Fixed-focal (3.6mm)
- H.265/H.264
- 2688*1522 Mainstream resolution
- Built-in microphone
- IP67

Specifications

Model	OTRARG400WHDI(M)
Camera	
Image Sensor	1/3" 4MP CMOS Sensor
Resolution	4MP
Effective Pixels	2688(H)*1522(V)
Lens	3.6mm
Compression	H.265/H.264
LUX	Color 0.05Lux@F1.2; B&W 0.005Lux@F1.2
S/N	≥50db(AGC OFF)
WDR	DWDR: >80db
Audio	
Audio/Intercom Input	Audio MIC Input
Audio Output	Built-in power magnify circuit
LED Type	CDS IR / Sensor Control / Warm LED / Extra add LED drive board (Optional)
Other Function	IRCU, Reset
Extension Function	Extension with IO
Network	
Main Stream	2560*1440, 1-25fps/s
	2304*1296 、 1920*1080 、 1280*720,1-30fps/s
Sub Stream	704*576 、 640*480 、 640*360 、 352*288,1-30fps/s
Video Coding Compression	128Kbps-8192bps Continuous Adjustable
Subtitle Overlay	Support Channel Name & Data & Time & Frame & Resolution & 4 Lines of Character Overlay
Data Transmission & Storage	
Data Record	Video & Picture
Storage Method	Cycling Recording & Alarm Recording
Alarm Transfer	Brower & Management Software, App
Protocol	ONVIF

Browser	Support IE Brower & Management Software Viewing
Mobile	WANAN App/IOS/Android
Technical Specifications	
Temperature	-30°C ~ +60°C
Humidity	0% - 90%
Protection	IP67
Power	DC12V/150mA
Dimensions	Φ 111 x 63(H) mm
Consumption	< 2W

Dimensions

